

Perfect Doorphone choice for daily life

Sometimes running or replacing cables is not cost effective or near impossible especially in older apartment buildings or established homes or businesses. A cost-effective alternative is to use the mobile networks to bypass cables altogether. Akuvox's Video Doorphone R29C-L is designed to remove cables from the solution solving what has become an expensive problem for many.



At a Glance

- Enables audio and visual monitoring of doors/gates which increase security on residential or commercial premises;
- Dual camera for anti-counterfeit, completely solve all kinds of photos and video deception on various carries;
- Face verification accuracy >99% ; face comparison speed <0.6s per person; false recognition rate<0.1%;
- Allows both audio and video communication to an IP phone, mobile client, or softphone;
- Enables the ability to remotely control the door/gate;
- Speeds response time to visitors, delivery and service personnel that require access;
- Using LTE technology to combine minimum installation when installed at sites;

Physical & Power

- | | |
|--|---|
| <ul style="list-style-type: none"> • Front panel: Aluminum • RAM / ROM: 2GB / 16GB • Display: 7 Inch IPS LCD • Screen: 7 Inch capacitive touch screen • Main Camera: 3M pixels, automatic lighting • Auxiliary Camera: 1M pixels • Light sensor: Support • Infrared sensor: Support • Wiegand ports: Support • RS485 ports: Support • RF card reader: 13.56MHz & 125kHz • Relays In/out: 2/2 | <ul style="list-style-type: none"> • Microphone: -32dB • Speaker: 8Ω / 2W • Bluetooth: Support • Ethernet port: RJ45, 10/100Mbps adaptive • SIM Card Slot: Support • 12V DC connector • Water-proof & Dust-proof: IP65 • Installation: Wall-mounted • Wall-mounted DIM: 324x130x41mm • Working Humidity: 10~90% • Working Temperature: -20°C ~ +55°C • Storage Temperature: -40°C ~ +70°C |
|--|---|

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711 μ , G.729
- Broadband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833),
SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/3", CMOS
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080p
- Max. image transfer rate: 1080p – 25fps
- Viewing angle: 120°(H) / 64°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- White LEDs for QR code scanning
- Compatible to 3rd-Party-Video components, e.g. NVRs

Network Connection

- LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18 /B19/B20/B25/ B26/B28
- LTE-TDD: B38/B39/B40/B41
- WCDMA: B1/B2/B4/B5/B6/B8/B19

Door Entry Feature

- Android OS for any 3rd party software or customization
- Relays controlled individually by DTMF tones
- Multi-way Unlock: Face, IC/ID Card, PIN and BLE
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control
- Business information or a welcome experience for guests