Akuvox R25A

Datasheet

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R25A enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

(((=))) (((=))) Akuvox

At a Glance

- Single speed-dial button with blue backlight;
- Linux operation system;
- Wide-angle camera: 150° (H), 150° (V);
- Two-way audio communication over IP networks with Echo Cancellation & Noise suppression;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

Physical & Power

Front panel: Aluminum

Camera: 4M pixels, automatic lighting

Button: 1 call button

Light sensor: Support

Motion sensor: Support

Wiegand port: Support

RS485 port: Support

RF card reader: 13.56MHz & 125kHz, NFC

Relays out: 2

• Inputs: 2

Microphone: 1

• Speaker: 1

Tamper alarm: Support

Ethernet port: RJ45, 10/100Mbps adaptive

802.3af Power-over-Ethernet

• IP Rating: IP65

• Size: 145x85x24.8mm

Installation: Flush-mounted or Wall-mounted

Working Humidity: 10~90%

Working Temperature: -40°C ~ +55°C

Storage Temperature: -40°C ~ +70°C



Akuvox R25A

Datasheet

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833),
 SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/3.2", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p, 2K
- Video codec: H.264
- Video resolution: up to 2000x2000
- Max. image transfer rate: 2K 30fps
- Viewing angle: 150°(H) / 150°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd party video components,
 e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

Protocols support: IPv4, HTTP, HTTPS, FTP,
 DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP,
 ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control

